

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Original) Wiper device (1) to wipe a windshield (5) of a motor vehicle with a wiper arm (10) and two connecting rod levers (8), wherein the connecting rod levers (8) are connected to the wiper arm (10) in a plane at fastening points (9) so they can move rotationally, wherein at least one of the connecting rod levers (8) is executed to be elastic essentially perpendicular to the wiper plane in order to effect a pressure force from the wiper arm (10) on the windshield.
2. (Original) Wiper device (1) according to Claim 1, wherein one of the connecting rod levers (8) is a drive lever (81) and another of the connecting rod levers (8) is a control lever (82), wherein the wiper arm (10) is moved by swiveling the drive lever (81) around a swivel axis (11).
3. (Previously Presented) Wiper device (1) according to Claim 1, wherein the wiper arm is designed to be non-articulated.
4. (Previously Presented) Wiper device according to Claim 1, wherein at least one of the connecting rod levers (8) is pre-stressed in an installed state.
5. (Previously Presented) Wiper device (1) according to Claim 1, wherein the wiper arm (10) is connected to a wiper blade (12) via a swivel joint.

6. (Previously Presented) Wiper device (1) according to Claim 1, wherein the connecting rod levers (8) each feature a fold-out mechanism in order to swivel the wiper arm (10) into a maintenance position [so] that a wiper blade (12) connected to the wiper arm (10) can be serviced or replaced, wherein the connecting rod levers (8) are designed such that in the maintenance position they are able to project at an angle from the wiper plane so the wiper arm (10) is accessible.
7. (Original) Wiper device (1) according to Claim 6, wherein the connecting rod levers each feature a snap-in device (17) in order to hold the connecting rod levers (8) in the maintenance position, wherein the connecting rod levers are designed such that they are able to exit the maintenance position by moving the connecting rod levers back into the wiper plane with a restoring force.
8. (Previously Presented) Wiper device (1) according to Claim 1, wherein the fastening parts of the connecting rod levers (8) and/or the connecting rod levers (8) are manufactured of a deep-drawing material.
9. (Previously Presented) Wiper device (1) according to Claim 1, wherein the connecting rod levers (8) are coupled with the wiper arm (10) at the fastening points with a caulked fastening element (16).
10. (Previously Presented) Wiper device according to Claim 1, wherein at least one of the connecting rod levers (8) is provided with a first cross-section in a first section facing the swivel axis and a second smaller cross-section in a second section facing the fastening point in order to adjust the pressure force.
11. (Previously Presented) Wiper device (1) according to Claim 2, wherein the wiper arm is designed to be non-articulated.
12. (Previously Presented) Wiper device according to Claim 11, wherein at least one of the connecting rod levers (8) is pre-stressed in an installed state.

13. (Previously Presented) Wiper device (1) according to Claim 12, wherein the wiper arm (10) is connected to a wiper blade (12) via a swivel joint.
14. (Previously Presented) Wiper device (1) according to Claim 13, wherein the connecting rod levers (8) each feature a fold-out mechanism in order to swivel the wiper arm (10) into a maintenance position so that a wiper blade (12) connected to the wiper arm (10) can be serviced or replaced, wherein the connecting rod levers (8) are designed such that in the maintenance position they are able to project at an angle from the wiper plane so the wiper arm (10) is accessible.
15. (Previously Presented) Wiper device (1) according to Claim 14, wherein the connecting rod levers each feature a snap-in device (17) in order to hold the connecting rod levers (8) in the maintenance position, wherein the connecting rod levers are designed such that they are able to exit the maintenance position by moving the connecting rod levers back into the wiper plane with a restoring force.
16. (Previously Presented) Wiper device (1) according to Claim 15, wherein the fastening parts of the connecting rod levers (8) and/or the connecting rod levers (8) are manufactured of a deep-drawing material.
17. (Previously Presented) Wiper device (1) according to Claim 16, wherein the connecting rod levers (8) are coupled with the wiper arm (10) at the fastening points with a caulked fastening element (16).
18. (Previously Presented) Wiper device according to Claim 17, wherein at least one of the connecting rod levers (8) is provided with a first cross-section in a first section facing the swivel axis and a second smaller cross-section in a second section facing the fastening point in order to adjust the pressure force.